



COMBI 30-36

Pantalla curvada máxima
visión 360°.

Écran de protection
VISIBILITÉ 360 degrés.

Curved protection visor for
360 degree visibility.




Paneles extraíbles.
Panneaux extractibles.
Removeable panels.

Novedoso sistema
tensor correas más
fácil y rápido.
Nouveau système de
tension de courroies
rapide.
New easy and quick
belt tightening system.

Clavija conexión protegida
internamente antigolpes.
Prise de courant interne anti-chocs.
Internally mounted power socket
to reduce wear and tear.



Novedoso sistema tensor
correas más fácil y rápido.
Nouveau système de
tension de courroies
rapide.
New easy and quick belt
tightening system.



Parada de emergencia
regulable antigolpes.
Arrêt d'urgence réglable
anti chocs.
Emergency stop.

Características / Caractéristiques / Characteristics



	Kg	C.V./HP Kw	R.P.M.	LxAxH	LxAxH	R.P.M. x1'	L
COMBI 30/36	435	4 3	1500	910x1033x1141	950x1070x1050	10	10

Dotación / Fourni de série / Included with machine



	1	4	4	1	1	1	1	1	1	2
COMBI 30/36										

Capacidad de doblado / Capacité de cintrage / Bending capacity

Límite elástico Limite élastique Yield strength	R=N/mm ² 250			R=N/mm ² 480			R=N/mm ² 650											
	1	2	3	1	2	3	1	2	3									
Resistencia tracción Résist. à la traction Tensile strength	R=N/mm ² 450			R=N/mm ² 650			R=N/mm ² 850											
Nºx	1	2	3	1	2	3	1	2	3									
COMBI 30/36	Ø30	Ø20	Ø16	Ø36	Ø26	Ø22	Ø25	Ø18	Ø14	Ø32	Ø24	Ø18	Ø25	Ø16	Ø12	Ø32	Ø22	Ø16



Visera protección
antigolpes y
salpicaduras.
Visière de protection du
cadre de commande anti-
chocs et éclaboussures.
Protection visor for
command centre.